

INTERNAL COMBUSTION AEOLIPILE

BACKGROUND

Since jet nozzles can extract mechanical energy from expanding combustion gases at much higher temperatures than turbine blades, the compression and fuel/air ratios may be greatly increased in an engine that expands combustion gases through a nozzle instead of the conventional axial turbine. Higher temperatures provide higher efficiencies and, in the aircraft engine embodiment, allow much higher top end speeds for aircraft and missiles compared to current turbojet engines. The problem is to obtain rotational shaft work to drive the compressor and generators by expanding a gas through one or more nozzles.

BRIEF SUMMARY OF THE INVENTION

In the present invention an aeolipile attached to an annular rotor internal stator compressor replaces the axial turbine of gas turbine engines. Rotational shaft work in the reaction turbine is produced from expanding the combustion gases directly through a plurality of jets or nozzles tangential to the circumference of the rotating engine. The annular rotor of the compressor is spin balanced along with the combustion chamber and the rest of the rotating engine while the stator houses the fuel line, hydraulics, electrical lines and other control systems. The engine is mounted wholly or in part on the compressor stator axle.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross section of an embodiment of the engine with a turbine 8 to recover additional energy from the jets 2. The jets rotate the engine which is attached to compressor rotor 6 supported by load bearing bladed wheels 22 mounted on the stator axle 24. Air enters the compressor at 20 and then mixes with fuel from fuel nozzles 14 in the combustion chamber 12. After combustion the gases expand through the jets. Fuel, electrical and other lines enter the engine through the open end of the stator axle 16. The turbine may be reverse geared to the aeolipile through gear box 10 so all the shaft work leaves through drive shaft 18.

FIG. 2 is a cross section of an aircraft "aeolifan" embodiment of the engine. Gases leave combustion chamber 52 and exit through the aeolipile jets 42 to drive the compressor and fan and, depending on how the main jet control 58 is set, for forward thrust. Air enters the annular area 62 for the fan or into the compressor intake 62. The entire engine is mounted on the stator axle 56.

FIG. 3 is a cross section of an embodiment of the engine with tip mounted combustion chambers 94. Fuel is delivered through the axle 96 to the combustion chambers by rotating fuel lines and by a means 80 to distribute the fuel from the stationary axle to the rotating lines.

March 5, 2001

Bret Cahill
P. O. Box 6322
Beaumont, TX 77725
409-833-2741
BretCahill@aol.com